Granito 60 Rust


Ernesto Gismondi



IP65 (≟) **《** [∏] .







LUMINAIRE

- Power Supply: **Electronic**

- Watt: **35W**

- Voltage: 220V-240V

Notes

Notices The product is manufactured using corten steel plate. Corten steel is coated with a natural oxide layer that becomes 'stable' 16/24 months from installation. Before stabilisation, corten steel may release rust powder that may stain the surfaces where it is placed. Artemide recommends not to position it on sensitive surfaces such as lightcoloured stone, marble, etc. Appearance The colour of corten steel may change in time depending on weather conditions and exposure to sunlight. The colour becomes stable after 16/24 and takes on a 'tobacco' hue. Care The product received a treatment that reduces, but does not eliminate, release of rust powder. If necessary, this treatment should be repeated by the customer until oxide stabilisation. Apply wood- care bee's wax using a soft cloth.

DESCRIPTION

Outdoor lamp. The four light beams projected through the fissures on the sides make it particularly suitable for lighting drives or to create light effects in parks and gardens. Cor-ten (weathering steel) structure, which is distinguished for its high resistance to corrosion and high mechanical resistance.

PRODUCT CODE: T083100

FEATURES

- Article Code: **T083100**

- Colour: Rust - Installation: Floor

- Material: Cor-ten steel, glass - Series: Architectural Outdoor

- Environment: Outdoor - Area contract: null

- Emission: Direct

- design by: Ernesto Gismondi

DIMENSIONS

- Width: cm 30 - Height: cm 60

- Impact Resistance: IK10

NOT INCLUDED SOURCES

- Category: HQI - Number: 1 - Lbs: HIT-CE

- Watt: **35W** - Socket: G12

- Color Rendering: 80

- Color temperature (K): 3000K




Granito 30 Rust

Ernesto Gismondi



IP65 😩 🕊 [[][📐



LUMINAIRE

- Power Supply: **Electronic**

- Watt: **35W**

- Voltage: 220V-240V

- CCT: 3000K

Notes

Notices The product is manufactured using corten steel plate. Corten steel is coated with a natural oxide layer that becomes 'stable' 16/24 months from installation. Before stabilisation, corten steel may release rust powder that may stain the surfaces where it is placed. Artemide recommends not to position it on sensitive surfaces such as light-coloured stone, marble, etc. Appearance The colour of corten steel may change in time depending on weather conditions and exposure to sunlight. The colour becomes stable after 16/24 and takes on a 'tobacco' hue. Care The product received a treatment that reduces, but does not eliminate, release of rust powder. If necessary, this treatment should be repeated by the customer until oxide stabilisation. Apply wood-care bee's wax using a soft cloth.

DESCRIPTION

Outdoor lamp. The four light beams projected through the fissures on the sides make it particularly suitable for lighting drives or to create light effects in parks and gardens. Cor-ten (weathering steel) structure, which is distinguished for its high resistance to corrosion and high mechanical resistance.

PRODUCT CODE: T083000

FEATURES

- Article Code: **T083000**

Colour: RustInstallation: Floor

Material: Cor-ten steel, glassSeries: Architectural Outdoor

Environment: OutdoorArea contract: nullEmission: Direct

- design by: Ernesto Gismondi

DIMENSIONS

Width: cm 30Height: cm 30

- Impact Resistance: IK10

NOT INCLUDED SOURCES

Category: HQINumber: 1Lbs: HIT-CEWatt: 35W

- Socket: **G12**

- Color Rendering: 80

- Color temperature (K): 3000K

