

DA 2668

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



- Customised kitchen design – fully integrated in 580 mm width
- Unique user convenience – Con@ctivity
- Powerful – 585 m<sup>3</sup>/h on the booster setting
- Energy-efficient and quiet – powerful ECO motor
- Efficient filtration- 10-ply stainless-steel grease filter

A+

EAN: 4002516001522 / Material number: 10851380 / Old Material Number: 28266855GB

<b>Construction type</b>	
Integrated extractor	•
<b>Operating modes</b>	
Type of air guide	Convertible
Recirculation conversion kit (order separately)	DUU 151
Active charcoal filter (order separately)	DKF 19-P
<b>Design</b>	
Colour	Stainless steel
Edge extraction	•
<b>User convenience</b>	
Miele@home	•
Automatic function Con@ctivity 3.0 (WiFi)	•
Electronic controls	•
Power levels (number without Booster level)	3
Miele@mobile app	•
Programmable Booster level switch-off	•
Run-on time 5/15 min.	•
Grease filter saturation indicator	•
Grease filter saturation indicator programmable	•
Active charcoal filter saturation indicator programmable	•
<b>Efficiency and sustainability</b>	
Energy efficiency class (A+++ to D)	A+
Annual energy consumption in kWh/year	28.4
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	A
ECO motor	•
PowerManagement system	•
<b>Cleaning convenience</b>	
Easy-to-clean canopy interior – CleanCover	•
<b>Filter system</b>	
Number of dishwasher-safe stainless steel grease filters (10-ply)	2
<b>Lighting</b>	
LED	•
Number x W	2 x 4,5 W
Light intensity in Lx	700 lx
Colour temperature in K	3500 Kelvin
Dimmer function	•
<b>Blower</b>	
Dual-action fan	•
DC motor	•
<b>Extraction</b>	
Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591	175
Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591	265
Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591	365
Air throughput in Booster level (m <sup>3</sup> /h) according to EN 61591	585
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	35.0

DA 2668

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002516001522 / Material number: 10851380 / Old Material Number: 28266855GB

Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	64.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	44.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	51.0
Noise pressure level in Intensive level (dB(A) re 20 µPa) according to EN 60704-2-13	50.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	21.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	29.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	37.0
<b>Recirculation</b>	
Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591	115
Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591	200
Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591	330
Air throughput in Booster level (m <sup>3</sup> /h) according to EN 61591	490
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	46.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	56.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	64.0
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	74.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	32.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	42.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	49.0
Sound pressure in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	60.0
<b>Safety</b>	
Safety switch-off	•
<b>Technical data</b>	
Canopy width in mm	580
Canopy height in mm	63
Canopy depth in mm	293
Net weight in kg	12.0
Length of supply lead in m	1.5
Standard plug fitted	•
Minimum height above electric hobs in mm	450
Minimum safety distance above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
Total rated load in kW	0.08
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Frequency in Hz	50

DA 2668

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002516001522 / Material number: 10851380 / Old Material Number: 28266855GB

#### Installation notes

Extraction ducting connection at top

•

Extraction connection at top and rear

•

Diameter of exhaust duct in mm

150

Combination with WiFi-enabled Miele hob

recommended

#### Optional accessories

Active charcoal filter

Nein