

# Wind

Design by Jordi Vilardell.

## Reference

**4057.**

## Application

Outdoor lamps

## Installation type

Surface Canopy

## Description

Floor lamp for outdoor use. Designed by Jordi Vilardell. The choice of a material, glass fibre, which is produced industrially by means of an innovative use of filament winding technology, gives this collection an appearance which unites technology with tradition.

## Diffuser

Methacrylate diffuser

## Materials

Diffuser: Methacrylate

Lid: Steel

Weight: Concrete

## Finish



**4057-27** Brown L1 (NCS S 1505-Y50R)




**4057-53** Green M1 (NCS S 6005-G80Y)



**4057-61** Ocre Red (NCS S 3050-Y60R)

## Sketch



## Electrical characteristics

1 x LED PLATE 25W 700mA



Total 25.0 W



# VIBIA



**Light source:** 2700K CRI >90 3480 lm 139.2 lm/W

**Fixture:** 741 lm 29 lm/W

**Driver included:** CC - Constant Current 700 mA 110~240V 50/60Hz

**Electronic dimming** ON/OFF

## Technical characteristics

- Portable version

## Physical characteristics

2 Box / 2.11 x 0.60 x 0.64 m. / Vol. 1.0885 m<sup>3</sup> /

Gross weight 44.7 kg. / Net weight 40.2 kg.

## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 36.07 lm/W

Coordinate system : CG

Total flux : 741.34 lm

Maximum value : 317.81 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

