

KM 3010 Gas hob with 4 burners



- Simple controls -single-handed operation via rotary dial control
- Elegant design 626 mm wide gas on glass hob
- Versatile 4 burners
- Extremely safe GasStop function
- Easy cleaning dishwasher-safe ComfortClean pot rests

EAN: 4002515055830 / Material number: 09101190 / Old Material Number: 26301050GB

Heating type	-
Heating type	Gas
Construction type	
Independent of cooker	•
Design	
Ceramic surface colour	Black
Cast iron pot rests (matt black enamelled)	•
Miele logo embossed in stainless steel	•
Cooking zone details	
Number of cooking zones	4
1st cooking zone/cooking area	
Position	front left
Type	High-speed burner
Max. rating in W	2700
2nd cooking zone/cooking area	
Position	rear left
Туре	Economy burner
Max. rating in W	1000
3rd cooking zone/cooking area	
Position	rear right
Туре	Standard burner
Max. rating in W	1700
4th cooking zone/cooking area	
Position	front right
Type	Standard burner
Max. rating in W	1700
User convenience	1700
Operation via knobs	•
Electronic ignition with single-hand operation	
Cleaning convenience	
Dishwasher-proof pot rests	•
Safety	•
GasStop & ReStort	- -
GasStop & ReStart	•
Technical data	54 ·· COC ·· FOC
Dimensions (W x H x D) in mm	54 x 626 x 526
Dimensions in mm (width)	626
Dimensions in mm (height)	54
Dimensions in mm (depth)	526
Cutout dimensions in mm (width) with surface-mounted	600
installation	- 62
Casing height incl. connection box in mm	63
Cutout dimensions in mm (depth) with surface-mounted installation	500
Weight in kg	17
Total rated load in kW	7.10
Length of supply lead in m	1.4
Voltage in V	220-240
Frequency in Hz	50-60



KM 3010 Gas hob with 4 burners




EAN: 4002515055830 / Material number: 09101190 / Old Material Number: 26301050GB

Accessories supplied	
Number of mains cables with plug	No
Jets for liquid gas	•

Míele

KM 3010 Gas hob with 4 burners



KM 3010 G (Installation drawing)

1. Front, 2. Casing depth, 3. Mains connection box with mains connection cable L = 2000 mmm, 4. Gas connection R 1/2" – ISO 7-1 (DIN EN 10226)