
# Calipso Linear System 120 Ceiling - APP Compatible

### Neil Poulton







#### LUMINAIRE

- Watt: 43W

- Delivered lumens output: 2985lm

- CCT: **3000K**- Efficiency: **58%**- Efficacy: **69.41lm/W** 

- CRI: **90** 

- Dimmable Typology: Push & APP

#### Notes

APP driver can not be controlled by a DALI dimming/Push system and viceversa.

In any APP configurations there must be only one App module (master) while the others must be DALI.

#### DESCRIPTION

The unique honeycomb grill of Calipso was generated by feeding a photo of the moon into an image-based algorithm found on a seemingly extinct computer. The resulting fractal shape, an impure geometry that displays the irregular beauty of nature, is built from an organic honeycomb of different diameter tubes, seemingly arranged in a random geometry. This honeycomb characterizes the lamp both aesthetically and optically - not only is it visually pleasing, but it also provides an even and comfortable light emission. The result is a highly emotional lighting object that joins together optical and aesthetic intelligence. A product positioned perfectly half-way between home and professional use, Calipso is suited to a variety of applications - expressing Artemide's traditional approach to deliver high performance lighting with a unique and emotional expressiveness.

#### PRODUCT CODE: 2011010APP

#### **FEATURES**

- Article Code: 2011010APP

Colour: WhiteInstallation: Ceiling

- Material: Technopolymer, aluminium

- Series: Design Collection, Architectural Indoor

Environment: Indoordesign by: Neil Poulton

#### DIMENSIONS

Length: cm 116.2Width: cm 7.9Height: cm 7.2

#### **SOURCES INCLUDED**

Category: LedNumber: 1Watt: 39W

Delivered lumens output: 4800lmColor temperature (K): 3000K

- CRI: 90

Efficacy: 123lm/WService Life: 50000-L70



Intermediate linear joint - Ceiling - It allows to mechanically connect two modules in-line 2025010A



Device for switching and controlling Artemide App products. Max N.3 inputs for external push buttons. Mains power supply required. To be installed inside flush mounting boxes or junction boxes. DV1080APP



End cap kit - Ceiling (2 pcs) 2026010A






# Calipso Linear System 180 Ceiling - APP Compatible

### Neil Poulton







#### LUMINAIRE

- Watt: **63W** 

- Delivered lumens output: 4477lm

CCT: 3000KEfficiency: 58%Efficacy: 71.07lm/W

- CRI: **90** 

- Dimmable Typology: Push & APP

#### Notes

APP driver can not be controlled by a DALI dimming/Push system and viceversa.

In any APP configurations there must be only one App module (master) while the others must be DALI.

#### **DESCRIPTION**

The unique honeycomb grill of Calipso was generated by feeding a photo of the moon into an image-based algorithm found on a seemingly extinct computer. The resulting fractal shape, an impure geometry that displays the irregular beauty of nature, is built from an organic honeycomb of different diameter tubes, seemingly arranged in a random geometry. This honeycomb characterizes the lamp both aesthetically and optically - not only is it visually pleasing, but it also provides an even and comfortable light emission. The result is a highly emotional lighting object that joins together optical and aesthetic intelligence. A product positioned perfectly half-way between home and professional use, Calipso is suited to a variety of applications - expressing Artemide's traditional approach to deliver high performance lighting with a unique and emotional expressiveness.

#### PRODUCT CODE: 2012010APP

#### **FEATURES**

- Article Code: 2012010APP

Colour: WhiteInstallation: Ceiling

- Material: Technopolymer, aluminium

- Series: Design Collection, Architectural Indoor

Environment: Indoordesign by: Neil Poulton

#### DIMENSIONS

Length: cm 173.6Width: cm 7.9Height: cm 7.2

#### **SOURCES INCLUDED**

Category: LedNumber: 1Watt: 58,3W

Delivered lumens output: **7200lm**Color temperature (K): **3000K** 

- CRI: 90

- Efficacy: **123lm/W** 

- Service Life: 50000-L70



Intermediate linear joint - Ceiling - It allows to mechanically connect two modules in-line 2025010A



Device for switching and controlling Artemide App products. Max N.3 inputs for external push buttons. Mains power supply required. To be installed inside flush mounting boxes or junction boxes. DV1080APP



End cap kit - Ceiling (2 pcs) 2026010A





# Calipso Linear System 120 Ceiling

## Neil Poulton







#### **LUMINAIRE**

- Watt: 43W

- Delivered lumens output: 2985lm

- CCT: **3000K**- Efficiency: **58%** 

- Efficacy: 69.41lm/W

- CRI: 90

- Dimmable Typology: Push/DALI

#### Notes

APP driver can not be controlled by a DALI dimming/Push system and viceversa.

In any APP configurations there must be only one App module (master) while the others must be DALI.

#### DESCRIPTION

The unique honeycomb grill of Calipso was generated by feeding a photo of the moon into an image-based algorithm found on a seemingly extinct computer. The resulting fractal shape, an impure geometry that displays the irregular beauty of nature, is built from an organic honeycomb of different diameter tubes, seemingly arranged in a random geometry. This honeycomb characterizes the lamp both aesthetically and optically - not only is it visually pleasing, but it also provides an even and comfortable light emission. The result is a highly emotional lighting object that joins together optical and aesthetic intelligence. A product positioned perfectly half-way between home and professional use, Calipso is suited to a variety of applications - expressing Artemide's traditional approach to deliver high performance lighting with a unique and emotional expressiveness.

#### PRODUCT CODE: 2011010A

#### **FEATURES**

- Article Code: 2011010A

Colour: WhiteInstallation: Ceiling

- Material: Technopolymer, aluminium

- Series: Design Collection, Architectural Indoor

Environment: Indoordesign by: Neil Poulton

#### **DIMENSIONS**

Length: cm 116.2Width: cm 7.9Height: cm 7.2

#### **SOURCES INCLUDED**

Category: LedNumber: 1Watt: 39W

Delivered lumens output: 4800lmColor temperature (K): 3000K

- CRI: 90

Efficacy: 123lm/WService Life: 50000-L70



Intermediate linear joint - Ceiling - It allows to End cap kit - Ceiling (2 pcs) 2026010A mechanically connect two modules in-line 2025010A






# Calipso Linear System 180 Ceiling

## Neil Poulton







#### LUMINAIRE

- Watt: 63W

- Delivered lumens output: 4477Im

- CCT: **3000K**- Efficiency: **58%** 

- Efficacy: **71.07lm/W** 

- CRI: 90

- Dimmable Typology: Push/DALI

#### Notes

APP driver can not be controlled by a DALI dimming/Push system and viceversa.

In any APP configurations there must be only one App module (master) while the others must be DALI.

#### DESCRIPTION

The unique honeycomb grill of Calipso was generated by feeding a photo of the moon into an image-based algorithm found on a seemingly extinct computer. The resulting fractal shape, an impure geometry that displays the irregular beauty of nature, is built from an organic honeycomb of different diameter tubes, seemingly arranged in a random geometry. This honeycomb characterizes the lamp both aesthetically and optically - not only is it visually pleasing, but it also provides an even and comfortable light emission. The result is a highly emotional lighting object that joins together optical and aesthetic intelligence. A product positioned perfectly half-way between home and professional use, Calipso is suited to a variety of applications - expressing Artemide's traditional approach to deliver high performance lighting with a unique and emotional expressiveness.

#### PRODUCT CODE: 2012010A

#### **FEATURES**

- Article Code: 2012010A

Colour: WhiteInstallation: Ceiling

- Material: Technopolymer, aluminium

- Series: Design Collection, Architectural Indoor

Environment: Indoordesign by: Neil Poulton

#### **DIMENSIONS**

Length: cm 173.6Width: cm 7.9Height: cm 7.2

#### **SOURCES INCLUDED**

Category: LedNumber: 1Watt: 58,3W

Delivered lumens output: 7200lmColor temperature (K): 3000K

- CRI: 90

Efficacy: 123lm/WService Life: 50000-L70



Intermediate linear joint - Ceiling - It allows to mechanically connect two modules in-line 2025010A

End cap kit - Ceiling (2 pcs) 2026010A





# Calipso Linear System 60 Ceiling

## Neil Poulton







#### LUMINAIRE

- Watt: 22W

- Delivered lumens output: 1492lm

- CCT: **3000K**- Efficiency: **58%** 

- Efficacy: **67.84lm/W** 

- CRI: 90

- Dimmable Typology: Push/DALI

#### Notes

APP driver can not be controlled by a DALI dimming/Push system and viceversa.

In any APP configurations there must be only one App module (master) while the others must be DALI.

#### DESCRIPTION

The unique honeycomb grill of Calipso was generated by feeding a photo of the moon into an image-based algorithm found on a seemingly extinct computer. The resulting fractal shape, an impure geometry that displays the irregular beauty of nature, is built from an organic honeycomb of different diameter tubes, seemingly arranged in a random geometry. This honeycomb characterizes the lamp both aesthetically and optically - not only is it visually pleasing, but it also provides an even and comfortable light emission. The result is a highly emotional lighting object that joins together optical and aesthetic intelligence. A product positioned perfectly half-way between home and professional use, Calipso is suited to a variety of applications - expressing Artemide's traditional approach to deliver high performance lighting with a unique and emotional expressiveness.

#### PRODUCT CODE: 2010010A

#### **FEATURES**

- Article Code: **2010010A** 

Colour: WhiteInstallation: Ceiling

- Material: Technopolymer, aluminium

- Series: Design Collection, Architectural Indoor

Environment: Indoordesign by: Neil Poulton

#### **DIMENSIONS**

Length: cm 58.8Width: cm 7.9Height: cm 7.2

#### **SOURCES INCLUDED**

Category: LedNumber: 1Watt: 19,4W

Delivered lumens output: 2400lmColor temperature (K): 3000K

- CRI: 90

Efficacy: 124lm/WService Life: 50000-L70



Intermediate linear joint - Ceiling - It allows to
mechanically connect two modules in-line
2025010A

End cap kit - Ceiling (2 pcs) 2026010A



