
Led Net Line 125 - Suspension - App Compatible

Michele De Lucchi Alberto Nason



DESCRIPTION





LUMINAIRE

- Watt: 45W

- Voltage: 220-240V

- Delivered lumens output: 2530lm

CCT: 3000KEfficiency: 78%Efficacy: 56.22lm/W

- CRI: 80

Notes

It's a sectional unit that enables elements to be added (supplied as special project).

PRODUCT CODE: 1578050APP

FEATURES

Article Code: 1578050APPColour: Polished whiteInstallation: Suspension

- Material: Aluminium, methacrylate

- Series: **Design Collection**

- Environment: **Indoor**

- Area contract: **Hospitality, null**

- Emission: Direct

- design by: Michele De Lucchi, Alberto Nason

DIMENSIONS

Length: cm 125Width: cm 28.5Height: cm 2.4

- Max Height from ceiling: cm 200

- Glow Wire Test: 650°

SOURCES INCLUDED



PRODUCT DATA SHEET

PRODUCT CODE: 1578050APP

Category: LedNumber: 18Watt: 2.17W

Delivered lumens output: 153ImColor temperature (K): 3000K

- CRI: **80**

- Color Tolerance: MacAdam 3SDCM

- Efficacy: 71lm/W

- Service Life: **50000-L70**

Accessories



Device for switching and controlling Artemide App products. Max N.3 inputs for external push buttons. Mains power supply required. To be installed inside flush mounting boxes or junction boxes. DV1080APP



Led Net Line 125 - Ceiling - App Compatible

Michele De Lucchi Alberto Nason



DESCRIPTION

IP20 ⊕ **《** (€ •



LUMINAIRE

- Watt: 45W

- Voltage: 220-240V

- Delivered lumens output: 2530lm

- CCT: 3000K - Efficiency: 78%

- Efficacy: 56.22lm/W

- CRI: 80

Notes

LEDs included

PRODUCT CODE: 1596050APP

FEATURES

- Article Code: **1596050APP** - Colour: Polished white

- Installation: Ceiling

- Material: Aluminium, methacrylate

- Series: Design Collection

- Environment: Indoor

- Area contract: Hospitality, null

- Emission: **Direct**

- design by: Michele De Lucchi, Alberto Nason

DIMENSIONS

- Length: cm 140 - Width: cm 32.4 - Height: cm 7

- Glow Wire Test: 650°

SOURCES INCLUDED



PRODUCT DATA SHEET

PRODUCT CODE: 1596050APP

Category: LedNumber: 18Watt: 2.17W

Delivered lumens output: **153lm**Color temperature (K): **3000K**

- CRI: **80**

- Color Tolerance: MacAdam 3SDCM

- Efficacy: 71lm/W

- Service Life: **50000-L70**

Accessories



Device for switching and controlling Artemide App products. Max N.3 inputs for external push buttons. Mains power supply required. To be installed inside flush mounting boxes or junction boxes. DV1080APP

