





4395



4395 Folding table

High levels of mobility and flexibility, combined with an excellent price-performance ratio – this is what distinguishes the model 4395 folding table. The table top can be folded back with one turn of the hand, while the large rollers also facilitate handling, allowing a single person to convert the table within seconds.



Frame

T-base frame, column and foot stabilizers made from \emptyset 40 x 2 mm tubular metal, soldered together, mounted on four black double rollers with parking brakes, transversal beam made from \emptyset 40 x 2 mm tubular metal, folding mechanism made from glass-fibre reinforced black plastic, equipped with a central release mechanism.

Frame surfaces

Standard version: power-coated in black, optionally powder-coated according to the BRUNE® collection or chrome-plated.


Table tops

Plate C: 30 mm thick, high-quality multi-layer plywood plate E1, top surface optionally covered with HPL plastic or wood veneer according to the BRUNE® collection. Lower surface white HPL or beech veneer. Straight edge, 2 mm thick, in material to match table top (plastic for plastic, veneer for veneer).

Plate D: 30 mm thick, 28 mm thick high-quality multi-layer plywood plate E1, top surface optionally covered with HPL plastic or wood veneer according to the BRUNE® collection. Lower surface white HPL or beech veneer. Edge with solid beechwood edge band, smooth finish, 9 mm thick.

Plate E: 30 mm thick, 28 mm high-quality multi-layer plywood board E1, coated in high-pressure laminate (HPL) or veneer according to the BRUNE® collection. Lower surface: white HPL or beech veneer. Edge: solid beech edge band, crowned, 9 mm thick.







Veneer finish

Real wood veneer from the BRUNE® collection comes as a standard varnished with a low solvent content water-based lacquer, optionally stained to the BRUNE® collection.

HPL surfaces

Resopal®-HPL from the BRUNE® collection.

Rollers

Double plastic rollers with parking brake.



Note

For the configuration of several tables as a connected table system, we recommend the use of optional table connectors 4001, 4004, for table depths of 70 cm and more also 4003. For the attachment of the table connectors, please provide us with a layout plan.

Dimensions

Table Height: 75 cm

Table sizes: min. 60 cm

max. 180 cm

Weights: 140x70 cm 29 kg

160x70 cm 32 kg 180x70 cm 36 kg 140x80 cm 32 kg 160x80 cm 36 kg 180x80 cm 40 kg

Certificates



www.tuv.com ID 0000065977

TÜV Certificate



Quality management in accordance with DIN EN ISO 9001



Environmental management system in accordance with DIN EN ISO 14001