

## Product Information

# PEPPER

Design Uwe Sommerlade



**PEPPER | Model 2470 without armrests | Model 2475 + Model 2478 with armrests**

The noble design is impressive thanks to its clarity and grace. PEPPER captivates due to discreet elegance and timeless modernity. With its ergonomic shape, high degree of material quality and perfect finishing, PEPPER guarantees relaxed sitting in every situation.

## Areas of use

---

HEALTHCARE SERVICES | SEMINARS | MEETINGS | RESTAURANTS + FINE DINING | CAFETERIAS + STAFF CANTEENS | CHURCH | LIVING |

## Frame

---

Frame made of solid beech, with round cross-sectional area ca. 22-37 mm tapered, frame solid beech in rectangular profile ca. 28 x 63 mm. Front and rear panels made from curved beech, cleats und frame completely dowelled, mortised and bonded.

## Frame surfaces

---

Wooden elements made from beech wood, with natural varnish (low-solvent water varnish) in the standard version. Optionally stained according to the BRUNE® collection.

## Seat shell

---

Ergonomically shaped solid shell made from beech plywood, 10 mm thick, multi-bonded, back area slightly tapered out at the top. Attachment of the plywood shell on the base frame cap screws and threaded sockets M6. Optionally fully upholstered, with partial upholstery on the seat or continuous partial upholstery shell, no visible screws.

## Upholstery – seat shell with seat padding

---

Seat cushion foam:                      RG/SH 35/50                      ca. 20 mm thick

SG = specific gravity, weight per m<sup>3</sup>. CH = compression hardness (e.g.: 50  $\triangleq$  approx. 50 g/cm<sup>2</sup> at a compression level of 40 %)

## Upholstery – seat shell with front side padding

---

Seat cushion foam:                      RG/SH 35/50                      ca. 20 mm thick

Back cushion foam:                      RG/SH 35/50                      ca. 15 mm thick

SG = specific gravity, weight per m<sup>3</sup>. CH = compression hardness (e.g.: 50  $\triangleq$  approx. 50 g/cm<sup>2</sup> at a compression level of 40 %)

## Upholstery – seat shell fully upholstered

---

Seat cushion foam:                      RG/SH 35/50                      ca. 25 mm thick

Back cushion foam (front):              RG/SH 35/50                      ca. 20 mm thick

Back cushion foam (back):              RG/SH 35/50                      ca. 5 mm thick


SG = specific gravity, weight per m<sup>3</sup>. CH = compression hardness (e.g.: 50  $\triangleq$  approx. 50 g/cm<sup>2</sup> at a compression level of 40 %)

## Gliders

Standard version:	plastic gliders
Optionally:	felt gliders
Optionally:	metal gliders

## Dimensions | 2470 without armrests, stackable


Dimensions:	B	53 cm
	T	56 cm
	H	89 cm
	SH	45 cm



Weights:	5,5 kg
	6 kg (seat padding)
	6,5 kg (front side padding)
	6 kg (fully upholstered)

## Dimensions | 2475 with armrests, stackable


Dimensions:	B	65 cm
	T	56 cm
	AH	67 cm
	H	89 cm
	SH	45 cm



Weights:	7 kg
	7,5 kg (seat padding)
	8 kg (front side padding)
	7,5 kg (fully upholstered)

## Dimensions | 2478 with armrests, non stackable

Dimensions:	B	57 cm
	T	56 cm
	AH	67 cm
	H	89 cm
	SH	45 cm



Weights:	7 kg
	7,5 kg (seat padding)
	8 kg (front side padding)
	7,5 kg (fully upholstered)

## Stackability

---

Stacking type:	front stapling, stackable	5 chairs
	On transport carriage for oblique stacking 1997	10 chairs
Required floor space:	Length:	82 cm
	Width:	59 cm
	Height:	134 cm
On transport carriage 1997	Length:	98 cm
	Width:	59 cm
	Height:	155 cm



## Accessories

---

Chair trolley:	Model 1996 for the transport of stacked chairs
Transport carriage for oblique stacking:	Model 1997 for the transport of stacked chairs

## Certificates

---



Quality management in accordance with DIN EN ISO 9001

Environmental management system in accordance with DIN EN ISO 14001

## Awards

---

