

KM 2357-1

Gas hob

with electronic functions for maximum safety and user convenience.



- Optimal – single-handed operation via rotary dials and QuickStart
- Professional design – 892 mm wide stainless steel trough
- Particularly versatile – 5 burners incl. 1 dual wok
- Extremely safe – GasStop&Restart function
- Easy cleaning – dishwasher-safe ComfortClean pot rests

EAN: 4002516120094 / Material number: 10940180 / Old Material Number: 26235761GB

Heating type	
Heating type	Gas
Construction type	
Independent of cooker	•
Design	
Cast iron pot rests (matt black enamelled)	•
Miele logo embossed in stainless steel	•
Flush-fit stainless steel hob	•
Cooking zone details	
Number of cooking zones	5
1st cooking zone/cooking area	
Position	front left
Type	Economy burner
Max. rating in W	1000
2nd cooking zone/cooking area	
Position	rear left
Type	High-speed burner
Max. rating in W	2700
3rd cooking zone/cooking area	
Position	Centred
Type	Dual wok burner
Max. rating in W	4500
4th cooking zone/cooking area	
Position	rear right
Type	Standard burner
Max. rating in W	1700
5th cooking zone/cooking area	
Position	front right
Type	Standard burner
Max. rating in W	1700
User convenience	
Operation via knobs	•
Electronic ignition with single-hand operation	•
QuickStart	•
Cleaning convenience	
Dishwasher-proof pot rests	•
Safety	
GasStop & ReStart	•
Technical data	
Dimensions in mm (width)	892
Dimensions in mm (height)	105
Casing height incl. connection box in mm	101
Dimensions in mm (depth)	512
Cutout dimensions in mm (width) with surface-mounted installation	880
Cutout dimensions in mm (depth) with surface-mounted installation	500
Internal cutout dimensions in mm (depth) with flush installation	500
Weight in kg	20

KM 2357-1

Gas hob

with electronic functions for maximum safety and user convenience.



EAN: 4002516120094 / Material number: 10940180 / Old Material Number: 26235761GB

External cutout dimensions in mm (width) with flush installation	892
External cutout dimensions in mm (depth) with flush installation	512
Total rated load in kW	0.00
Internal cutout dimensions in mm (width) with flush installation	880
Length of supply lead in m	1.4
Voltage in V	220-240
Frequency in Hz	50-60
Accessories supplied	
Number of mains cables with plug	No
Jets for liquid gas	•
Wok ring	•
Small trivet	•