

DAS 4630  
Slimline cooker hood  
with intuitive SmartControl controls



- Elegant design – obsidian black control panel, 60 cm wide
- Unique user convenience – Con@ctivity
- LED strip for uniform lighting
- Efficient filtration- 10-ply stainless-steel grease filter
- Recirculation mode – Active AirClean or Longlife AirClean filter



EAN: 4002516496151 / Material number: 11878210 / Old Material Number: 28S4630BGB

<b>Construction type</b>	
Slimline cooker hood	•
<b>Operating modes</b>	
Type of air guide	Convertible
Recirculation conversion kit (order separately)	DUU 151
<b>Design</b>	
Colour	Obsidian black
<b>User convenience</b>	
Miele@home	•
Automatic function Con@ctivity 3.0 (WiFi)	•
Electronic controls	•
Touch-on-glass controls	•
Programmable Booster level switch-off	•
Run-on time 5/15 min.	•
Grease filter saturation indicator	•
Grease filter saturation indicator programmable	•
Active charcoal filter saturation indicator programmable	•
<b>Efficiency and sustainability</b>	
Energy efficiency class (A+++ to D)	A+++
Annual energy consumption in kWh/year	23.5
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	A
PowerManagement system	•
ECO motor	•
<b>Cleaning convenience</b>	
Easy-to-clean canopy interior – CleanCover	•
<b>Filter system</b>	
Number of dishwasher-safe stainless steel grease filters (10-ply)	1
<b>Lighting</b>	
LED	•
Number x W	1 x 3 W
Light intensity in lx	330 lx
Colour temperature in K	3500 Kelvin
Dimmer function	•
<b>Blower</b>	
Dual-action fan	•
DC motor	•
<b>Extraction</b>	
Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591	180
Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591	280
Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591	400
Air throughput in Booster level (m <sup>3</sup> /h) according to EN 61591	600
Air throughput in Booster level (m <sup>3</sup> /h) according to EN 61591	720
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	38.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	48.0

DAS 4630  
Slimline cooker hood  
with intuitive SmartControl controls



EAN: 4002516496151 / Material number: 11878210 / Old Material Number: 28S4630BGB

Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	56.0
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	66.0
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	70.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	25.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	34.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	42.0
Sound pressure in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	53.0
Sound pressure in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	57.0
<b>Recirculation</b>	
Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591	165
Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591	265
Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591	380
Air throughput in Booster level (m <sup>3</sup> /h) according to EN 61591	585
Air throughput in Booster level (m <sup>3</sup> /h) according to EN 61591	695
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	43.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	53.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	62.0
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	72.0
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	77.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	29.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	40.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	48.0
Sound pressure in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	59.0
Sound pressure in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	63.0
<b>Safety</b>	
Safety switch-off	•
Single-ply safety glass (ESG)	•
<b>Technical data</b>	
Canopy width in mm	596
Canopy height in mm	36
Canopy depth in mm	273
Minimum height above electric hobs in mm	450
Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650


DAS 4630  
Slimline cooker hood  
with intuitive SmartControl controls



EAN: 4002516496151 / Material number: 11878210 / Old Material Number: 28S4630BGB

Net weight in kg	12.0
Length of supply lead in m	1.5
Standard plug fitted	•
Total rated load in kW	0.16
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Frequency in Hz	50
<b>Installation notes</b>	
Extraction ducting connection at top	•
Diameter of exhaust duct in mm	150
<b>Accessories supplied</b>	
Non-return flap	•
<b>Optional accessories</b>	
Active charcoal filter	Nein

DAS 4630  
Slimline cooker hood  
with intuitive SmartControl controls



DAS4630, Installation drawings

1) The front section of the wall unit must be fitted with a base panel to secure the cooker hood. If the appliance is fitted further back, e.g. to accommodate a front panel, then the shelf depth should be deeper accordingly. . 2) If a partition wall is to be provided in the unit, it must be removable. . 3) Extraction, recirculation with conversion kit DUU 150. . \* In this installation situation, the deflector plate is flush with the front edge of the housing unit carcass. . If you wish to position the cooker hood further forward or further back, dimensions have to be adapted accordingly. . Extraction: the height of the wall unit and the cut-out dimensions must take into account any accessories fitted, e.g. silencer, recirculation hood conversion kit).