

## PUR 98 D

### Island cooker hood

with energy-efficient LED lighting and light-touch switches for easy use.



- Timeless design – 898 mm wide stainless steel cooker hood
- Powerful – 650 m<sup>3</sup>/h on the booster setting
- Efficient filtration- 10-ply stainless-steel grease filter
- Safe and easy to clean – Miele CleanCover
- Suitable for every home – for extraction or recirculation

A

EAN: 4002516585794 / Material number: 12050650 / Old Material Number: 28410858GB

<b>Construction type</b>	
Wall mounted cooker hood	•
<b>Operating modes</b>	
Type of air guide	Convertible
<b>Design</b>	
Colour	Stainless steel
<b>User convenience</b>	
Electronic controls	•
<b>Efficiency and sustainability</b>	
Energy efficiency class (A+++ to D)	A
Annual energy consumption in kWh/year	51.8
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	A
<b>Filter system</b>	
Number of dishwasher-safe stainless steel grease filters (10-ply)	3
<b>Lighting</b>	
Number x W	4 x 3 W
Light intensity in lx	500 lx
Colour temperature in K	3000 Kelvin
<b>Blower</b>	
Dual-action blower	•
AC motor	•
<b>Extraction</b>	
Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591	280
Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591	330
Air throughput in Intensive level (m <sup>3</sup> /h) according to EN 61591	650
Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591	400
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	48.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	53.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	57.0
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	69.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	31.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	35.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	39.0
Sound pressure in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	51.0
<b>Recirculation</b>	
Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591	190
Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591	270
Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591	330
Air throughput in Booster level (m <sup>3</sup> /h) according to EN 61591	460

## PUR 98 D

### Island cooker hood

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002516585794 / Material number: 12050650 / Old Material Number: 28410858GB

Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	57.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	62.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	66.0
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	73.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	40.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	45.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	49.0
Sound power in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	56.0
<b>Safety</b>	
Safety switch-off	•
<b>Technical data</b>	
Canopy width in mm	898
Overall height for vented and external in in. (mm)	690
Overall height for extraction mode and external mode cooker hoods in mm	990
Overall height for recirculation in in. (mm)	750
Overall height for recirculation mode cooker hoods in mm	1060
Canopy height in mm	70
Canopy depth in mm	598
Net weight in kg	34.0
Length of supply lead in m	0.0
Minimum height above electric hobs in mm	450
Minimum safety distance above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
Total rated load in kW	0.23
Hard-wired connection	•
Voltage in V	230
Fuse rating in A	10
Frequency in Hz	50
Number of phases	1
<b>Installation notes</b>	
Extraction ducting connection at top	•
Diameter of exhaust duct in mm	150
Telescopic chimney	•
<b>Optional accessories</b>	
Active charcoal filter	Nein