

DA 6698 W Purist. Ed.6000

Wall mounted cooker hood

with energy-efficient LED lighting and touch controls for simple operation.



- Family design – based on Miele built-in appliances
- Unique user convenience – Con@ctivity
- Powerful – 640 m³/h on the booster setting
- Energy-efficient and quiet – powerful ECO motor
- Pleasantly quiet – Miele Silence package

A++

EAN: 4002516585275 / Material number: 12050610 / Old Material Number: 28669851GB

Construction type	
Wall mounted cooker hood	•
Operating modes	
Type of air guide	Convertible
Design	
Colour	Stainless steel
User convenience	
Electronic controls	•
Silence package	•
Efficiency and sustainability	
Energy efficiency class (A+++ to D)	A++
Annual energy consumption in kWh/year	24.6
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	A
ECO motor	•
PowerManagement system	•
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	3
Lighting	
Number x W	3 x 3 W
Light intensity in lx	670 lx
Colour temperature in K	3500 Kelvin
Blower	
Dual-action blower	•
DC motor	•
Extraction	
Air throughput in Level 1 (m ³ /h) according to EN 61591	200
Air throughput in Level 2 (m ³ /h) according to EN 61591	300
Air throughput in Intensive level (m ³ /h) according to EN 61591	640
Air throughput in Level 3 (m ³ /h) according to EN 61591	400
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	36.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	44.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	52.0
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	63.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	21.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	29.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	37.0
Sound pressure in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	48.0
Recirculation	
Air throughput in Level 1 (m ³ /h) according to EN 61591	110
Air throughput in Level 2 (m ³ /h) according to EN 61591	185

DA 6698 W Purist. Ed.6000

Wall mounted cooker hood

with energy-efficient LED lighting and touch controls for simple operation.



EAN: 4002516585275 / Material number: 12050610 / Old Material Number: 28669851GB

Air throughput in Level 3 (m ³ /h) according to EN 61591	315
Air throughput in Booster level (m ³ /h) according to EN 61591	460
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	45.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	53.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	63.0
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	72.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	30.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	38.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	48.0
Sound power in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	57.0
Safety	
Safety switch-off	•
Single-ply safety glass (ESG)	•
Technical data	
Canopy width in mm	898
Overall height for vented and external in in. (mm)	710
Overall height for extraction mode and external mode cooker hoods in mm	1030
Overall height for recirculation in in. (mm)	840
Overall height for recirculation mode cooker hoods in mm	1160
Canopy height in mm	85
Canopy depth in mm	500
Net weight in kg	26.0
Length of supply lead in m	1.5
Standard plug fitted	•
Minimum height above electric hobs in mm	450
Minimum safety distance above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
Total rated load in kW	0.08
Voltage in V	230
Fuse rating in A	10
Frequency in Hz	50
Number of phases	1
Installation notes	
Extraction ducting connection at top	•
Extraction connection at top and rear	•
Diameter of exhaust duct in mm	150
Telescopic chimney	•
Optional accessories	
Active charcoal filter	Nein