

DA 2578
Extractor unit
with energy-efficient LED lighting and light-touch switches for easy use.

Construction type



- Customised kitchen design fully integrated in 702 mm width
- Unique user convenience Con@ctivity
- Powerful 600 m3/h on the booster setting
- Efficient filtration- 10-ply stainlesssteel grease filter
- Safe and easy to clean Miele CleanCover



Construction type	
Integrated extractor	•
Operating modes	
Type of air guide	Convertible
Recirculation conversion kit (order separately)	DUU 151
Active charcoal filter (order separately)	DKF 15-P
Design	
Colour	Stainless steel
User convenience	
Miele@home	•
Automatic function Con@ctivity 3.0 (WiFi)	•
Electronic controls	•
Power levels (number without Booster level)	3
Miele@mobile app	•
Programmable Booster level switch-off	•
Run-on time 5/15 min.	•
Grease filter saturation indicator	•
Grease filter saturation indicator programmable	•
Active charcoal filter saturation indicator programmable	•
Efficiency and sustainability	
Energy efficiency class (A+++ to D)	A
Annual energy consumption in kWh/year	51.7
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	В
Cleaning convenience	
Easy-to-clean canopy interior - CleanCover	•
Filter system	
Number of dishwasher-safe stainless steel grease filters	2
(10-ply)	
Lighting	
LED	
Number x W	2 x 3 W
Light intensity in Lx	300 lx
Colour temperature in K	3000 Kelvin
Blower	
Dual-action fan	
AC motor	•
Extraction	
Air throughput in Level 1 (m³/h) according to EN 61591	250
Air throughput in Level 2 (m³/h) according to EN 61591	300
Air throughput in Level 3 (m³/h) according to EN 61591	360
Air throughput in Booster level (m³/h) according to EN 61591	600

47.0

67.0

51.0

EAN: 4002515978276 / Material number: 10851350 / Old Material Number: 28257855GB

60704-3

60704-3

60704-3

Sound power in Level 1 (dB(A) re 1 pW) according to EN

Sound power in Booster level (dB(A) re 1 pW) acc. to EN

Sound power in Level 2 (dB(A) re 1 pW) according to EN



DA 2578 Extractor unit with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002515978276 / Material number: 10851350 / Old Material Number: 28257855GB

Noise pressure level in Intensive level (dB(A) re 20 μPa) according to EN 60704-2-13 52.0 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 32.0 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 37.0 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 41.0 Recirculation Air throughput in Level 1 (m³/h) according to EN 61591 200 Air throughput in Level 2 (m²/h) according to EN 61591 250 Air throughput in Level 3 (m³/h) according to EN 61591 320 Air throughput in Booster level (m³/h) according to EN 61591 320 Air throughput in Booster level (m³/h) according to EN 61591 530 Sound power in Level 1 (dB(A) re 1 pW) according to EN 61591 55.0 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 60.0 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 63.0 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 63.0 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 44.0 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 57.0 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 57.0 Sound pressur	Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	56.0
Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 Recirculation Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Evel 2 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 3 (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 61591 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 63.0 80704-3 Sound power in Booster level (dB(A) re 1 pW) according to EN 60704-3 Sound power in Booster level (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 20 μPa) according to EN 60704-2 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 Safety Safety Safety Safety switch-off • Technical data Canopy width in mm 702 Canopy height in mm 402 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm Net weight in kg Length of supply lead in m 51.5 Standard plug fitted • Total rated load in kW Voltage in V 230 Fuse rating in A Number of phases 1 Frequency in Hz Intellection of the EN 6000 pressure in the Park Park Park Park Park Park Park Park		52.0
EN 60704-2-13 Sound pressure in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Evel 2 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 61591 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 63.0 60704-3 Sound power in Booster level (dB(A) re 1 pW) according to EN 60704-3 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 Safety Safety Safety switch-off Technical data Canopy height in mm 50 Canopy height in mm 400 Minimum height above electric hobs in mm Net weight in kg In 6 Length of supply lead in m Net weight in kg Length of supply lead in m Net weight in kg Length of supply lead in m Net weight in kg Length of supply lead in m Net weight in kg Length of phases 1 Frequency in Hz Installation notes Extraction ducting connection at top	Sound pressure in Level 1 (dB(A) re 20 µPa) according to	32.0
EN 60704-2-13 Recirculation 200 Air throughput in Level 2 (m³/h) according to EN 61591 250 Air throughput in Level 3 (m³/h) according to EN 61591 320 Air throughput in Booster level (m³/h) according to EN 61591 320 Air throughput in Booster level (m³/h) according to EN 61591 530 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 55.0 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 63.0 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 63.0 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 39.0 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 44.0 EN 60704-2-13 44.0 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 48.0 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 57.0 EN 60704-2-13 48.0 Safety • Safety switch-off • Technical data • Canopy height in mm 402 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 450 Not weight in k		37.0
Air throughput in Level 1 (m³/h) according to EN 61591 200 Air throughput in Level 2 (m³/h) according to EN 61591 250 Air throughput in Level 3 (m³/h) according to EN 61591 320 Air throughput in Booster level (m³/h) according to EN 61591 530 61591 530 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 55.0 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 63.0 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 72.0 Sound power in Booster level (dB(A) re 20 μPa) according to EN 60704-3 39.0 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 44.0 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 44.0 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 57.0 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 57.0 Safety 55.0 Safety switch-off • Technical data • Canopy height in mm 402 Minimum height above electric hobs in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm • </td <td></td> <td>41.0</td>		41.0
Air throughput in Level 2 (m³/h) according to EN 61591 250 Air throughput in Level 3 (m³/h) according to EN 61591 320 Air throughput in Booster level (m³/h) according to EN 61591 530 61591 530 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 55.0 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 69.0 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 63.0 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 39.0 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 44.0 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 48.0 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 57.0 Safety 36 Safety switch-off • Technical data 702 Canopy height in mm 402 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 450 Net meight of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10	Recirculation	
Air throughput in Level 3 (m³/h) according to EN 61591 320 Air throughput in Booster level (m³/h) according to EN 61591 530 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 55.0 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 59.0 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 63.0 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 72.0 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 39.0 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 44.0 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 48.0 Salety 57.0 Safety 57.0 Safety witch-off • Technical data • Canopy width in mm 50 Canopy height in mm 402 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm • Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 </td <td>Air throughput in Level 1 (m³/h) according to EN 61591</td> <td>200</td>	Air throughput in Level 1 (m³/h) according to EN 61591	200
Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 72.0 60704-3 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 Safety Safety Safety Safety switch-off Technical data Canopy width in mm Canopy height in mm Canopy height in mm Canopy depth in mm 402 Minimum height above electric hobs in mm Met weight in kg Length of supply lead in m 1.5 Standard plug fitted Total rated load in kW 0.22 Voltage in V Everating in A Number of phases Extraction ducting connection at top	Air throughput in Level 2 (m³/h) according to EN 61591	250
61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 55.0 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 59.0 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 63.0 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 72.0 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 39.0 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 44.0 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 57.0 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 57.0 Safety 53.6 Safety switch-off • Technical data 702 Canopy width in mm 702 Canopy depth in mm 402 Minimum height above electric hobs in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650 Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of ph	Air throughput in Level 3 (m³/h) according to EN 61591	320
60704-3 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 59.0 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 63.0 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 72.0 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 39.0 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 44.0 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 57.0 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 57.0 Safety Safety switch-off Technical data 702 Canopy height in mm 50 Canopy depth in mm 402 Minimum height above electric hobs in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650 Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes 50		530
60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 63.0 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 72.0 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 39.0 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 44.0 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 57.0 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 57.0 Safety Safety Safety switch-off • Technical data 0 Canopy height in mm 702 Canopy depth in mm 402 Minimum height above electric hobs in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650 Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fruse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes •	· · · · · · · · · · · · · · · · · · ·	55.0
60704-3 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 72.0 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 39.0 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 44.0 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 57.0 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 57.0 Safety 53.6 Safety switch-off • Technical data 702 Canopy height in mm 50 Canopy depth in mm 402 Minimum height above electric hobs in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650 Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes 50 Extraction ducting connection at top •	· · · · · · · · · · · · · · · · · · ·	59.0
60704-3 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 39.0 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 44.0 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 57.0 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 57.0 Safety • Safety switch-off • Technical data 702 Canopy height in mm 50 Canopy depth in mm 402 Minimum height above electric hobs in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650 Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes 5 Extraction ducting connection at top •	· · · · · · · · · · · · · · · · · · ·	63.0
EN 60704-2-13 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 Safety Safety switch-off Technical data Canopy width in mm Canopy depth in mm 402 Minimum height above electric hobs in mm Net weight in kg Length of supply lead in m Net weight in kW Total rated load in kW Voltage in V Frequency in Hz Installation notes Extraction ducting connection at top 48.0 44.0 48.0 48.0 48.0 57.0		72.0
EN 60704-2-13 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 Safety Safety Safety switch-off Technical data Canopy width in mm Canopy height in mm Canopy depth in mm 402 Minimum height above electric hobs in mm Net weight in kg Length of supply lead in m Net weight in kg Total rated load in kW Voltage in V Fuse rating in A Number of phases Extraction ducting connection at top 48.0 4		39.0
EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13 Safety Safety switch-off Technical data Canopy width in mm Canopy height in mm 50 Canopy depth in mm 402 Minimum height above electric hobs in mm Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm Net weight in kg Length of supply lead in m Standard plug fitted Total rated load in kW Voltage in V Fuse rating in A Number of phases Extraction ducting connection at top 57.0 57		44.0
EN 60704-2-13 Safety Safety switch-off • Technical data Canopy width in mm 702 Canopy height in mm 50 Canopy depth in mm 402 Minimum height above electric hobs in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650 Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top •		48.0
Safety switch-off•Technical data702Canopy width in mm50Canopy height in mm402Minimum height above electric hobs in mm450Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm650Net weight in kg11.6Length of supply lead in m1.5Standard plug fitted•Total rated load in kW0.22Voltage in V230Fuse rating in A10Number of phases1Frequency in Hz50Installation notesExtraction ducting connection at top		57.0
Technical dataCanopy width in mm702Canopy height in mm50Canopy depth in mm402Minimum height above electric hobs in mm450Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm650Net weight in kg11.6Length of supply lead in m1.5Standard plug fitted•Total rated load in kW0.22Voltage in V230Fuse rating in A10Number of phases1Frequency in Hz50Installation notesExtraction ducting connection at top	Safety	
Canopy width in mm 702 Canopy height in mm 50 Canopy depth in mm 402 Minimum height above electric hobs in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650 Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top •	Safety switch-off	•
Canopy height in mm 50 Canopy depth in mm 402 Minimum height above electric hobs in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650 Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top •	Technical data	
Canopy depth in mm 402 Minimum height above electric hobs in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650 Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top •	Canopy width in mm	702
Minimum height above electric hobs in mm 450 Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650 Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top •	Canopy height in mm	_ 50
Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650 Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top •	Canopy depth in mm	402
power, burner ≤ 4.5 kW) in mm Net weight in kg 11.6 Length of supply lead in m 1.5 Standard plug fitted • Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top	Minimum height above electric hobs in mm	450
Length of supply lead in m 1.5 Standard plug fitted ● Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top	0 (650
Standard plug fitted Total rated load in kW O.22 Voltage in V 230 Fuse rating in A Number of phases 1 Frequency in Hz Installation notes Extraction ducting connection at top	Net weight in kg	11.6
Total rated load in kW 0.22 Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top	Length of supply lead in m	1.5
Voltage in V 230 Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top •	Standard plug fitted	•
Fuse rating in A 10 Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top •	Total rated load in kW	0.22
Number of phases 1 Frequency in Hz 50 Installation notes Extraction ducting connection at top •	Voltage in V	230
Frequency in Hz Installation notes Extraction ducting connection at top 50 •	Fuse rating in A	10
Installation notes Extraction ducting connection at top •	Number of phases	1
Extraction ducting connection at top •	Frequency in Hz	50
Extraction connection at top and rear		•
	Extraction connection at top and rear	•
Diameter of exhaust duct in mm 150	Diameter of exhaust duct in mm	150



DA 2578
Extractor unit
with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002515978276 / Material number: 10851350 / Old Material Number: 28257855GB

Combination with WiFi-enabled Miele hob	recommended
Optional accessories	
Active charcoal filter	Ja