

K 31222 Ui Built-under refrigerator Compactly designed with a practical interior layout.



- Optimum and maintenance-free LED lighting in compartment
- Door shelves can be cleaned in the dishwasher ComfortClean



EAN: 4002515952559 / Material number: 10799670 / Old Material Number: 36312220GB

Appliance category	
Refrigerator	•
Construction type	
Built-in appliance	•
Undercounter appliance	•
Door hinge	right
Convertible door hinging	•
User convenience	
ComfortClean	•
Controls	
Operating concept	PicTronic
Independent temperature regulation of fridge and freezer	No
zones	
Automatic SuperCool	•
No. of temperature zones	1
Fridge/Fridge section	
No. of shelves	4
of which dividable (FlexiBoard)	1
Number of inner door racks for tinned food	1
Door rack for bottles	1
Efficiency and sustainability	
Energy efficiency class (A–G)	F
Annual energy consumption in kWh	114.61
Energy consumption in 24 h in kWh	0.31
Safety	
Lock function	•
Acoustic door alarm	•
Technical data	
Technical data Niche width in mm min.	600
	600 600
Niche width in mm min.	
Niche width in mm min. Niche width in mm max.	600
Niche width in mm min. Niche width in mm max. Niche height in mm min.	600 820
Niche width in mm min. Niche width in mm max. Niche height in mm min. Niche height in mm max.	600 820 880
Niche width in mm min. Niche width in mm max. Niche height in mm min. Niche height in mm max. Niche depth in mm	600 820 880 550
Niche width in mm min. Niche width in mm max. Niche height in mm min. Niche height in mm max. Niche depth in mm Appliance width in mm	600 820 880 550 597
Niche width in mm min. Niche width in mm max. Niche height in mm min. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance height in mm	600 820 880 550 597 820
Niche width in mm min. Niche width in mm max. Niche height in mm min. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm	600 820 880 550 597 820 550
Niche width in mm min. Niche width in mm max. Niche height in mm min. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Weight in kg	600 820 880 550 597 820 550 33.2
Niche width in mm min. Niche width in mm max. Niche height in mm min. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Weight in kg Door hinge technology	600 820 880 550 597 820 550 33.2 Fixed door
Niche width in mm min. Niche width in mm max. Niche height in mm min. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Weight in kg Door hinge technology Max. door front weight – refrigerator, in kg	600 820 880 550 597 820 550 33.2 Fixed door 10
Niche width in mm min. Niche width in mm max. Niche height in mm min. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Weight in kg Door hinge technology Max. door front weight – refrigerator, in kg Climate class	600 820 880 550 597 820 550 33.2 Fixed door 10 SN-ST
Niche width in mm min. Niche width in mm max. Niche height in mm max. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance width in mm Appliance depth in mm Appliance depth in mm Weight in kg Door hinge technology Max. door front weight – refrigerator, in kg Climate class Refrigerator compartment in l	600 820 880 550 597 820 550 33.2 Fixed door 10 SN-ST 137
Niche width in mm min. Niche width in mm max. Niche height in mm max. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance width in mm Appliance depth in mm Appliance depth in mm Weight in kg Door hinge technology Max. door front weight – refrigerator, in kg Climate class Refrigerator compartment in l 4* freezer compartment in l	600 820 880 550 597 820 550 33.2 Fixed door 10 SN-ST 137 0
Niche width in mm min. Niche width in mm max. Niche height in mm min. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance width in mm Appliance depth in mm Appliance depth in mm Weight in kg Door hinge technology Max. door front weight – refrigerator, in kg Climate class Refrigerator compartment in l 4* freezer compartment in l Total usable capacity in l	600 820 880 550 597 820 550 33.2 Fixed door 10 SN-ST 137 0 136
Niche width in mm min. Niche width in mm max. Niche height in mm max. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Weight in kg Door hinge technology Max. door front weight – refrigerator, in kg Climate class Refrigerator compartment in I 4* freezer compartment in I Total usable capacity in I Storage time in case of fault in h Noise class (A–D)	600 820 880 550 597 820 550 33.2 Fixed door 10 SN-ST 137 0 136 0 B
Niche width in mm min. Niche width in mm max. Niche height in mm min. Niche height in mm max. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance height in mm Appliance depth in mm Weight in kg Door hinge technology Max. door front weight – refrigerator, in kg Climate class Refrigerator compartment in I 4* freezer compartment in I Total usable capacity in I Storage time in case of fault in h Noise class (A–D) Sound power in dB(A) re 1 pW	600 820 880 550 597 820 550 33.2 Fixed door 10 SN-ST 137 0 136 0 B 35
Niche width in mm min. Niche width in mm max. Niche height in mm max. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance width in mm Appliance height in mm Appliance depth in mm Weight in kg Door hinge technology Max. door front weight – refrigerator, in kg Climate class Refrigerator compartment in I 4* freezer compartment in I Total usable capacity in I Storage time in case of fault in h Noise class (A–D) Sound power in dB(A) re 1 pW Current consumption (mA)	600 820 880 550 597 820 550 33.2 Fixed door 10 SN-ST 137 0 136 0 B 35 1200
Niche width in mm min. Niche width in mm max. Niche height in mm max. Niche height in mm max. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance width in mm Appliance height in mm Appliance depth in mm Weight in kg Door hinge technology Max. door front weight – refrigerator, in kg Climate class Refrigerator compartment in I 4* freezer compartment in I Total usable capacity in I Storage time in case of fault in h Noise class (A–D) Sound power in dB(A) re 1 pW Current consumption (mA) Voltage in V	600 820 880 550 597 820 550 33.2 Fixed door 10 SN-ST 137 0 136 0 35 1200 220-240
Niche width in mm min. Niche width in mm max. Niche height in mm max. Niche height in mm max. Niche depth in mm Appliance width in mm Appliance width in mm Appliance height in mm Appliance depth in mm Weight in kg Door hinge technology Max. door front weight – refrigerator, in kg Climate class Refrigerator compartment in I 4* freezer compartment in I Total usable capacity in I Storage time in case of fault in h Noise class (A–D) Sound power in dB(A) re 1 pW Current consumption (mA)	600 820 880 550 597 820 550 33.2 Fixed door 10 SN-ST 137 0 136 0 B 35 1200



K 31222 Ui Built-under refrigerator Compactly designed with a practical interior layout.





EAN: 4002515952559 / Material number: 10799670 / Old Material Number: 36312220GB


Frequency in Hz	50
Length of supply lead in m	1.9
Replacing lamps	Customer Service
Accessories supplied	
Egg tray	•



K 31222 Ui Built-under refrigerator Compactly designed with a practical interior layout.







K31222Ui, K31225Ui, K31252Ui, K31242UiF, F31202Ui (installation drawings) K31222Ui, K31225Ui, K31252Ui, K31242UiF, F31202Ui, side view (installation drawings)

K31222Ui, K31225Ui, K31252Ui, K31242UiF, F31202Ui (installation drawings)