

KWT 6722 iGS-1 Built-in wine conditioning unit with FlexiFrame, SommelierSet and Push2open for demanding wine connoisseurs.



- Flexible storage of larger wine bottles thanks to FlexiFrame
- Perfect design for handleless kitchens Push2open
- Simultaneous wine storage in separate temperature zones
- Odourless refrigeration section thanks to Active AirClean filters
- Present your wine in the perfect light LED lighting



| Appliance category | |
|--|---------------------------|
| Wine conditioning unit | • |
| Construction type | |
| Built-in appliance | • |
| Integrated appliance | • |
| Door hinge | right |
| Convertible door hinging | • |
| Side-by-side enabled | • |
| Design | |
| Front colour | Glass door |
| Wine compartment lighting | LED illumination |
| User convenience | |
| Networking with Miele@home | • |
| Accessories required | XKS 3130 W |
| DynaCool | • |
| SoftClose | • |
| Concealed door opener | Push2open |
| Silence system | • |
| Number of shelves | 8 |
| Shelf material | Beechwood |
| Number of FlexiFrame racks | 8 |
| SommelierSet | • |
| NoteBoard | Yes |
| 3 D bottle presenter | • |
| Low-vibration storage | • |
| Control system | |
| Operating concept | TouchControl |
| Independent temperature regulation of fridge and freezer zones | No |
| No. of temperature zones | 2 |
| Min. temperature setting range in °C | |
| Max. temperature setting range in °C | 20 |
| Efficiency and sustainability | |
| Energy efficiency class (A-G) | G |
| Annual energy consumption in kWh | 165.00 |
| Energy consumption in 24 h in kWh | 0.45 |
| Safety | |
| | |
| Lock function | |
| , | • |
| Lock function Acoustic door alarm | • |
| Lock function Acoustic door alarm Acoustic temperature alarm | |
| Lock function Acoustic door alarm Acoustic temperature alarm Optical door alarm | • |
| Lock function Acoustic door alarm Acoustic temperature alarm Optical door alarm Optical temperature alarm | • |
| Lock function Acoustic door alarm Acoustic temperature alarm | • |
| Lock function Acoustic door alarm Acoustic temperature alarm Optical door alarm Optical temperature alarm Technical data Niche width in mm min. | • • • 560 |
| Lock function Acoustic door alarm Acoustic temperature alarm Optical door alarm Optical temperature alarm Technical data Niche width in mm min. Niche width in mm max. | • • • 560 570 |
| Lock function Acoustic door alarm Acoustic temperature alarm Optical door alarm Optical temperature alarm Technical data Niche width in mm min. | • • • 560 |



EAN: 4002516712350 / Material number: 12364310 /

KWT 6722 iGS-1 Built-in wine conditioning unit with FlexiFrame, SommelierSet and Push2open for demanding wine connoisseurs.

Active AirClean filter




| Old Material Number: 36672222EU1 | |
|--|------------|
| Appliance width in mm | 595 |
| Appliance height in mm | 1770 |
| Appliance depth in mm | 572 |
| Weight in kg | 94.0 |
| Climate class | SN |
| Wine compartment in I | 271 |
| Total usable capacity in I | 271 |
| 0.75 Bordeaux bottle capacity (no. of bottles) | 83 bottles |
| Acoustic airborne noise emission class (A–D) | В |
| Sound emissions in dB(A) re 1 pW | 32 |
| Current consumption (mA) | 1500 |
| Voltage in V | 220-240 |
| Fuse rating in A | 10 |
| Number of phases | 1 |
| Frequency in Hz | 50-60 |
| Length of supply lead in m | 2.8 |
| Accessories included | |




KWT 6722 iGS-1

Built-in wine conditioning unit


with FlexiFrame, SommelierSet and Push2open for demanding wine connoisseurs.



KWT6722iGS, KWT6722iGS-1, installation draw



KWT6722iGS, KWT6722iGS-1, side view (installation drawing)



KWT6722iGS, KWT6722GiS-1, Interior dimensions (Installation drawings)