

LINESCAPES CANTILEVERED

Family of floor, ceiling and wall lamps, efficient with an highly versatile linear luminous output. Structure in aluminium extruded and opal white polycarbonate diffuser. Horizontal cantilever wall version supplied with kit for connection with remote driver. White or black finishing with elements in grey painted on the floor and wall versions.



LED 2700K

LAMPING

Source	LINEAR LED
Total power	12W
Emission	DIFFUSED, ORIENTABLE
Tension	24V DC
Color temperature	2700K
Luminous flux	475lm (luminous output)
Typ CRI	85
Energy class	A+
Materials	aluminum + pc + abs
Notes	driver not included, recessing box included, wall board for installation included, side emission, orientable 340°, recessed hole 5"x4.3" depth 3.5"
Accessories	Lipari ring,

Codes

LIN LW2 34

Structure

white

PACKAGE

Package 01

Dimension: 7.9"x5.9"x57.1" inches

Certificazioni



LED 3000K

LAMPING

Source	LINEAR LED
Total power	12W
Emission	DIFFUSED, ORIENTABLE
Tension	24V DC
Color temperature	3000K
Luminous flux	475lm (luminous output)
Typ CRI	85
Energy class	A+
Materials	aluminum + pc + abs
Notes	driver not included, recessing box included, wall board for installation included, side emission, orientable 340°, recessed hole 5"x4.3" depth 3.5"
Accessories	Lipari ring,

Codes

LIN LWW 34

Structure

white

PACKAGE

Package 01

Dimension: 7.9"x5.9"x57.1" inches

Certificazioni

