


Nemea 2820

PEDRALI
THE ITALIAN ESSENCE

DESIGN
CMP Design

100% MADE IN ITALY



kg 5
lb 11.02



mc 0,37
ft³ 13.066



max 6 pcs

Nemea chair in ash wood with support in die-cast aluminium

Sedia Nemea in frassino con supporto in pressofusione di alluminio / Stuhl Nemea aus Esche mit Aluminiumdruckguss / Chaise Nemea en frêne avec support en aluminium moulé sous pression / Silla Nemea de fresno con soporte en fundición de aluminio

MATERIALS

Materiali
Materialien
Matériaux
Materiales

• FRAME - TELAIO - GESTELL - STRUCTURE - ARMAZÓN

FSC Ash

Frassino FSC / Esche FSC / Frêne FSC / Fresno FSC

SEAT - SEDUTA - SITZ - ASSISE - ASIENTO

Seat and backrest in ash plywood

Sedile e schienale in multistrato di frassino / Sitz und Rücken aus Eschen-Multiplex / Assise et dossier en contreplaqué de frêne / Asiento y respaldo de madera contrachapada de fresno

FINISH - FINITURA - AUSFÜHRUNG - FINITIONS - ACABADO

Water-based paint, matt finish (5 gloss), anti-scratch

Verniciatura a base acqua, finitura opaca (5gloss), antigraffio / Wasserlack, Ausführung matt (5glanz), kratzfest / Peinture à base d'eau, finition mate (5 gloss), anti-rayures / Pintura a base de agua, acabado mate (brillo 5), anti-arañazos



FR

N1

Lacquered visible grains

Laccato poro aperto / Laqué pore ouvert / Eiche offenporig lackiert / Lacado poro abierto



GC

BI

AN

BL2

AZ1

VE2

VE1

RB

RA

MO

MC

Wooden coming from FSC monitored and safeguarded forests

Legno proveniente da foreste controllate FSC / Holz aus FSC - kontrollierten Wäldern geerntet / Bois provenant des forêts contrôlées FSC / Madera extraída de bosques controlados por el FSC

• FRAME - SUPPORTO - ABSTÜTZUNG - SUPPORT - SOPORTE

Die-cast aluminium, epoxy-polyester powder coating

Pressofusione d'alluminio, verniciata con polvere epossipoliestere / Aluminium-Druckguss, epoxy-polyester pulverbeschichtet / Aluminium moulé sous-préssion, vernissage à poudre époxy-polyester / Fusión de aluminio, pintada con pintura en polvo epoxi-poliéster

FRAME FINISH - FINITURA SUPPORTO - AUSFÜHRUNG DES ABSTÜTZUNG - FINITION SUPPORT - ACABADO SOPORTE



BI200

NE

FEET - PIEDINI - GLEITER - PATINS - TACOS

Feet with interchangeable insert in felt type "20", suitable for delicate and sensitive floors (wood, ceramics, marble)

Piedini con inserto intercambiabile in feltro tipo "20", adatti per pavimenti delicati e sensibili (legno, ceramica, marmo) / Gleiter mit austauschbaren Einsatz aus Filz Typ "20", für sanfte und zartfühlende Boden geeignet (Holz, Keramik, Marmor) / Patins avec insert interchangeable en feutre type "20", pour sols délicats et sensibles (bois, marbre, céramique) / Tacos con inserto intercambiabile de fieltro tipo "20", aptos para pisos delicados y sensibles (madera, cerámica, mármol)

Reproduction of this document is strictly prohibited without prior written authorisation from Pedrali SpA. Sizes, weights and finishes may change without previous notice. È vietata la riproduzione del seguente documento senza previa autorizzazione scritta da parte di Pedrali SpA. Dimensioni, pesi e finiture possono variare senza alcun preavviso.

REGULATIONS AND CERTIFICATES

Normative e Certificazioni
Bestimmungen und Zertifikat
Normatives et certifications
Normativas y certificados

According to EN 16139:2013 level 2, extreme
EN di riferimento 16139:2013 livello 2, extreme

Seat and back static load test EN 1728:2012+AC:2013
Carico statico sul sedile e schienale EN 1728:2012+AC:2013

Seat and back fatigue test, 200.000 cycles EN 1728:2012+AC:2013
Resistenza a fatica del sedile-schienale, 200.000 cicli EN 1728:2012+AC:2013

CATAS CERTIFICATE - CERTIFICATO CATAS

Test report 205215

Rapporto di prova 205215 / Testbericht 205215 / Rapport d'essai 205215 / Prueba n° 205215

100% demountable product - 100% recyclable material

Prodotto 100% disassemblabile - 100% materiali riciclabili / Produkt 100% demontierbar - 100% Material recyclingfähig / Produit 100% démontable - 100% recyclable / Producto 100% desmontable - 100% materiales reciclables



The mark of
responsible forestry
FSC® C114358

CATAS