
GLOBE CONE FLOOR





Year of Design Material **LED Spec** Cable Spec Dimmability Rating/Location

Polycarbonate, steel and carbon fibre integrated, serviceable LED. 800 lumens. 3000K. CRI ≥ 80. 250cm/98.4in black fabric cable with foot switch

Mains dimmable.

IP20



GLOBE CONE FLOOR CHROME BLACK EU

Code GLS02CH-FEU02M1 Components GLS02CH CONF01BKEU

GLOBE CONE FLOOR COPPER BLACK EU

Code GLS02CO-FEU02M1 Components GLS02CO CONF01BKEU

GLOBE CONE FLOOR

Process

Blow moulded polycarbonate with a semi metallised interior and injection moulded polycarbonate diffuser.

Cleaning Instructions

Clean with a soft dry cloth only. Do not use polishing agents, water or abrasive materials when cleaning. Always switch off the electricity supply before cleaning.

Country of origin

Germany

Packaging

GLS02CH

Height 0.58 m Width 0.55 m Length 0.55 m Weight 3.7 kg

GLS02CO

Height 0.58 m 0.55 m Width 0.55 m Length Weight 3.7 kg

CONF01BKEU

Height 1.4 m Width 0.27 m Length 0.27 m Weight 6.5 kg

Product weight

10.2 kg

Requires assembly

Light Source Included


6W Tom Dixon LED Ring

Voltage 220-240V









tomdixon.net

2

