

Guise

Design by Diez Office.

Reference

2292.

Application

Ceiling Lamps

Installation type

Surface Canopy

Description

Ceiling light. The larger diameter glass cylinder is held vertically, concentrating the light within a lower corona of light. The pattern of striations etched into the borosilicate glass irradiates a general light with a moiré effect of visual interference crowned by a fine halo. The light source is hidden by the upper black profile.

Diffuser

Borosilicate glass diffuser

Materials

Ceiling rose: Steel

Body: Aluminum

Finish



2292-18 Graphite (ADAPTA RF 9913 WX)

Sketch




Electrical characteristics

1 x LED STRIP 24V 12W

Total 12.0 W



VIBIA



Light source: 3000K CRI >90 1325 lm 118 lm/W

Driver included: CV - Constant Voltage 110~240V 50/60Hz

Electronic dimming: 1-10V PUSH

Optional dimming: DALI or Casambi

Technical characteristics

- Sensor on the LED base

Physical characteristics

1 Box / 0.30 x 0.39 x 0.39 m. / Vol. 0.0444 m³ /

Gross weight 4.4 kg. / Net weight 2.2 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 26.02 lm/W

Coordinate system : C=0.00 G=0

Total flux : 398.74 lm

Maximum value : 329.76 cd

Light position : CG

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

