## Mayfair

Design by Diego Fortunato.

Reference

5510.

Application

Floor Lamps

Installation type

Surface Canopy

Description

The Mayfair lamps are a Diego Fortunato design proposal. The entire Mayfair collection incorporates LED lighting and comes in various finishes: green and orange.

Diffuser

Polycarbonate diffuser

Materials

Shade: Methacrylate Diffuser: Polyethylene Vertical tube: Steel Base: Zamak

Finish



**5510-07** Graphite and green (RAL 7016, RAL 6026)



**5510-08** Graphite and orange (RAL 7016, RAL 2009)

Sketch



**Electrical characteristics** 

1 x LED STRIP 24V 2.4W

AND

1 x LED STRIP 24V 12,6W

Total 15.0 W







Light source: 2700K CRI >80 1841 Im 96 Im/W

Fixture: 484 lm 0 lm/W

Driver included: CV - Constant Voltage 100~240V 50/60Hz

Electronic dimming SENSOR

**Technical characteristics** 

- 24V transformer at plug
- Touch sensitive dimmer swich on shade

**Physical characteristics** 

1 Box / 0.32 x 0.34 x 1.50 m. / Vol. 0.1632  $m^3\,/$ Gross weight 11.6 kg. / Net weight 10.4 kg.

Installation and assembly

Please, see the installation manual

Light distribution

## **Indirect lighting**

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.

Isolux: floor

Light position :


X=0.00m Y=0.00m Z=1.34m



Photometric data

Efficiency: 26.31% Coordinate system : CG Total flux: 1840.50

Maximum value: 66.01 Light position : C=45.00 G=40.00 Symmetry on the planes : Asymmetric



Certificates











