# Palma

Design by Antoni Arola.



Light source: 2700K CRI >90 Fixture: 685.5 lm 74.51 lm/W Driver included: CC - Constant Current 500 mA 110~240V 50/60Hz

Electronic dimming 1-10V PUSH Optional dimming: DALI

**Physical characteristics** 

1 Box / 0.45 x 0.31 x 0.33 m. / Vol. 0.0460 m<sup>3</sup> / Gross weight 4.0 kg. / Net weight 2.8 kg.

Installation and assembly Please, see the installation manual

Light distribution

## **General lighting**

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 1 Coordinate system : CG Total flux : 576.51 lm Maximum value : 67.81 cd/klm Light position : C=0.00 G=0.00 Isolux : Isolux (Floor) Light position : X=0.00m Y=0.00m Z=2.50m

Symmetry on the planes : Double symmetrical

Certificates

Total 9.2 W



Reference 3720.

Application

Hanging lamps

Installation type Surface Canopy

## Description

Vibia presents a pendant lamp. It includes two sizes of hand blown glass sphere joined together by a strap and aluminum structures. The intensity of the LED light source is dimmable.

### Diffuser

Blow-glass diffuser

Materials Profile: Aluminum Diffuser: Blown-glass

Finish

3720-18 Graphite (ADAPTA RF 9913 WX)

3720-93 White (RAL 9016)

Sketch



**Electrical characteristics** 2 x LED 4,6W 500mA

(ē)

A<sup>+</sup>

