

# Structural

Design by Arik Levy.

## Reference

**2600.**

## Application

Wall Lamps

## Installation type

Surface Canopy

## Description

Wall light with basic lines and cubic volumes that form sculptures integrated into the architecture.

## Diffuser

Polycarbonate diffuser

## Materials

Body: Aluminum  
Diffuser: Polycarbonate  
Profile: Aluminum

## Finish



**2600-15** Grey L2 (NCS S 2500-N)



**2600-21** Grey D1 (NCS S 7000-N)

## Sketch



## Electrical characteristics

# VIBIA



**Light source:** 3000K CRI >90

**Fixture:** 176 lm 29 lm/W

**Driver included:** CV - Constant Voltage 110~240V 50/60Hz

**Electronic dimming:** 1-10V

**Optional dimming:** DALI or Casambi

## Technical characteristics

- Only one main input by square box 16x16cm.

## Physical characteristics

1 Box / 0.17 x 0.27 x 0.27 m. / Vol. 0.0115 m<sup>3</sup> /  
Gross weight 1.5 kg. / Net weight 1.1 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting - opaque shade

Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



## Photometric data

Efficiency : 100.00%

Coordinate system : CG

Total flux : 176.90 lm

Maximum value : 159.34 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

