## Wind

Design by Jordi Vilardell.



Reference

## 4072.

Application

Outdoor lamps

Installation type

Surface Canopy

## Description

Hanging lamp for outdoor use. Designed by Jordi Vilardell. The choice of a material, glass fibre, which is produced industrially by means of an innovative use of filament winding technology, gives this collection an appearance which unites technology with tradition.

Diffuser

Methacrylate diffuser

Materials

Lid: Steel

Canopy Plate: Steel

Finish



4072-27 Brown L1 (NCS S 1505-Y50R)




4072-53 Green M1 (NCS S 6005-G80Y)



4072-61 Ocre Red (NCS S 3050-Y60R)

Sketch



**Electrical characteristics** 

1 x LED PLATE 25W 700mA



Total 25.0 W







Light source: 2700K CRI >90 3480 lm 139.2 lm/W

Fixture: 724 lm 28 lm/W

Driver included: CC - Constant Current 700 mA 110~240V 50/60Hz

Electronic dimming ON/OFF

**Physical characteristics** 

1 Box /  $0.50 \times 0.77 \times 0.77 \text{ m.}$  / Vol.  $0.2964 \text{ m}^3$  / Gross weight 11.1 kg. / Net weight 9.9 kg.

Installation and assembly

Please, see the installation manual

**Light distribution** 

## **General lighting**

Lamp for general lighting that equally distributes the light in all directions.




Photometric data

Efficiency: 35.51 lm/W Isolux: Floor Coordinate system : CG Light position : X=0.00m Y=0.00m Z=2.50m Total flux : 724.33 lm

Maximum value : 333.02 cd Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical



Certificates







